

CUSTOMER - SPECIFIC SOLUTIONSPROCESS PUMPS AND PUMPING SYSTEMS

With over 160 years of company history, Apollo is one of the most experienced manufacturers of customized, reliable, highquality pumps, plant equipment, and systems for process engineering. We provide the best possible technical solutions to our international customers in the energy, chemical, and oil and gas industries. Thanks to our comprehensive product range—which extends from product development to manufacturing system equipment and process pumps—we can support our customers throughout the entire planning process.











ENGINEERING | FABRICATION

We use modern methods of design and development, such as 3D CAD/CAM for creating casting patterns and finite element analysis for components, as well as simulations of the entire unit. Additionally, we use continuous hydraulic design with CFD software to create innovative pumps and system applications.

Apollo has modern machines with a high degree of automation which allows for efficient cooperation between all divisions. This allows for fast processing times and high manufacturing flexibility, as well as location protection.

TESTING

All of our Products can be tested according to the current valid norms and standards at our testing facilities up to 10 000 m³/h capacity range and 4 200 m pressure head, as well as drive powers up to 4,4 MW and voltage levels between 400 V and 13 KV. It is also possible to use a frequency converter for speed control of pump units on the test field.

QUALITY

Apollo's quality management system follows the ISO 9001 standard and includes comprehensive tests, analyses, and documentation of all of their manufactured products. These products are designed, manufactured, and tested according to standards such as API 610, DIN EN ISO or ANSI. The tests include material and component tests - mechanical, metallurgical as well as lifetime control, and failure analyses.

«Everything from one source under one roof»

Apollo develops and supplies customized fluid systems for a wide range of customer requirements. The principle of manufacturing engineered systems in relation with process pumps is based on many years of experience and highly graduated personnel.



THE RIGHT PUMP UNIT SOLUTION

FOR ANY REQUIREMENT

ENERGY INDUSTRY



OIL AND GAS INDUSTRY



OFFSHORE / **ONSHORE**



CHEMICAL INDUSTRY







FERTILIZER INDUSTRY



WATER **INDUSTRY**



RENEWABLE ENERGY



GENERAL INDUSTRY







COMMIS-SIONING / COMPLETE **ASSEMBLY** ON SITE



24/7 SITE SERVICE / **TECHNICAL SUPPORT**



MAINTE-NANCE



UPGRADE / **RETROFIT**



EDUCATION & TRAINING




SPARE PARTS

With the expertise gathered over many decades, we have specialized in the development and production of customer-specific pumps and pumping systems according to international industry standards as well as API 610. Based on synergies between pump manufacture and the in-house production of system technology and engineering plants, complete solutions can be provided from a single source.

HIGH QUALITY PROCESS PUMPS

Apollo develops and manufactures highly complex pumps and pumping systems for a wide range of industries and applications. The complete process chain can be offered, from engineering and mechanical processing to assembly, piping, electrical and control engineering. Customer-specific special requirements also present no problems at all.



OH1 - KRP / KRC

Horizontal, single-stage, radially split, heavy-duty foot-mounted pumps

Q (m ³ /h)	up to 2 800
H (m)	up to 250
P (bar)	up to 50 / 35
T (°C)	up to +220

OH2 - KRHL / KRPO / KGHL

Horizontal, single-stage/two-stage process pumps with semi-open impeller

Q (m ³ /h)	up to 45
H (m)	up to 350
P (bar)	up to 50
T (°C)	up to +450

OH2 - KRH / KRHA

Horizontal, single-stage, radially split, heavy-duty overhung pumps

Q (m ³ /h)	up to 5 000
H (m)	up to 320
P (bar)	up to 55 / 90
T (°C)	up to +450

OH3 - KRI / KRIL

Vertical, single-stage, radially split process pumps as inline version

Q (m³/h)	up to 800
H (m)	up to 270
P (bar)	up to 55
T (°C)	up to +250







BB1 - ZMK / ZMLK / ZMD

Heavy-duty, axially split, singlestage process pump, betweenbearings version

Q (m ³ /h)	up to 10 000
H (m)	up to 200
P (bar)	up to 25
T (°C)	up to +150

Heavy-duty, radially split, two-sta-

ge process pump between-be-

BB2 - KGR / KGRD

arings version

BB2 - ZPR / ZPRA

Horizontal, single-stage, double suction process pump, betweenbearings version

Q (m ³ /h)	up to 4 000
H (m)	up to 450
P (bar)	up to 160
T (°C)	up to +450




BB3 - AMG

Horizontal, multistage, axially split high-pressure pump betweenbearing version

Q (m ³ /h)	up to 3 200
H (m)	up to 2 200
P (bar)	up to 265
T (°C)	up to +200









BB4 - HP / GP / GH / GM / GL

Horizontal, multistage high-pressure pump of ring-section or back-to-back design

Q (m ³ /h)	up to 1 800
H (m)	up to 2 800
P (bar)	up to 300
T (°C)	up to +200



BB5 - TL / TG

Horizontal, multistage high-pressure pump of barrel design with inline rotor or back-to-back rotor

Q (m ³ /h)	up to 1 800
H (m)	up to 4 200
P (bar)	up to 450
T (°C)	up to +420



VS1 HPV / HPVX / GMV / GLV

Wet pit, vertically suspended, single-casing diffuser pumps

Q (m ³ /h)	up to 600
H (m)	up to 600
P (bar)	up to 63
T (°C)	up to +180
100	

VS4 KRHV / KRCV / KRPOV

Vertically suspended, single-casing, volute, line-shaft-driven sump pumps

Q (m ³ /h)	up to 500
H (m)	up to 280
P (bar)	up to 50
T (°C)	up to +250

VS6 HPTV / GSTV / GLKV / GDTV

Double-casing, diffuser, vertically suspended pumps of can-type

Q (m ³ /h)	up to 3 200
H (m)	up to 1 400
P (bar)	up to 140
T (°C)	up to -140 / +260







SULPHATE REMOVAL FEED PUMP acc. to API 610 | BB2 at oil platform in the North Sea

- APOLLO pump type: **ZPR-150/500-618/CN**
- Pump power: 694 kW (555 m³/h of 341 m)
- Material: super duplex acc. to NORSOK



RELIEF K.O. DRUM PUMP acc. to API 610 | OH2 at renewable process refinery complex

- APOLLO pump type: KRH-40C/350-308/CN
- Liquid: 200 °C Slop Oil
- with cooling equipment connected to the seal supply system and pump



SRP FEED PUMP acc. to API 610 | BB2 at oil platform in the North Sea

- APOLLO pump type: **ZPRV-150/500-618/CN**
- special design as vertical BB2 pump
- Pump power: 448 kW (445 m³/h of 279 m)



HGO / HVGO FEED PUMP acc. to API 610 | BB5 at renewable process refinery complex

- APOLLO pump type: TGD-80D/8-399/CN
- Liquid: 165 °C Heavy Vacuum Gas Oil
- Pump power: 1121 kW (168 m³/h of 2047 m)
- with lube oil system, Plan 53A system and cooling equipment, cartridge unit and with gear box





Apollo Gößnitz GmbH Walter-Rabold-Strasse 26 04639 Goessnitz / Germany

Phone: +49 (0) 34493 - 77 0 Fax: +49 (0) 34493 - 77 210 E-Mail: info@apollo-goessnitz.de

www.apollo-goessnitz.de